

Rainbow Silky Smooth Emulsion

Rainbow Silky Smooth Emulsion is top quality emulsion paint which is durable & washable. It is suitable for both interior & exterior surface with or without surface preparation.

Specification:

Composition	Based on high quality polyvinyl acetate acrylate resin combined with light fast pigment & suitable extenders.
Covering Capacity	300-325 Sq Meters /Gallon. (Complete Covering)
Film Thickness	25-35 Micron (Complete Covering)
Application	Brush, Roller and Spray
Number of Coats	2 or 3 Coats on prepared surface
Drying Time	2 Hours
	Recoatable 2 Hours
Thinner	Water 1:1
Flash Point	Not applicable
Gloss	Absolutely Matt Finish
Colour Range	as per Rainbow Silky smooth emulsion paint shade card
Packing	1, 4 and 16 Ltrs.

Application Guide

New Concrete Surface

Sand down the plaster with Emery Stone and apply one coat of Rainbow Water Based Primer. Prepare the surface by applying 2 Coats of Wall Putty followed by 2-3 Primer Sealer; apply 2-3 coats of Rainbow Silky Smooth Matt Emulsion Paint.

Old Painted Surfaces

Remove all dust, Dirt and loose adhering or flaked paints by scraping, apply one coats of Rainbow Water Base Primer followed by 2 coats of wall putty to smoothen the surface. For following paint apply 2-3 coats of Rainbow Silky Smooth emulsion.

Note: The above Information is given in good faith, but without any warranty.

Head Office:

CI-331, 16-B, Industrial Area,
North Karachi, Karachi.

Ph: 021-36971166, 36971167, Cell: 0321-2111328

Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Rainbow Paint Industries

Quality & Standard Paint Manufacturer

Regional Office:

House No. 5 Lane No. 1,
Scheme No. 02, PF Chowk

Tipu Road, Chaklala Rawalpindi

Ph: 051-5590971, 051-5591436, 051-5961401