

Rainbow Super Gloss Enamel

Rainbow Super Gloss Enamel is a top quality synthetic gloss finish. This is based on high quality synthetic resin and high quality light fast pigments. It has good gloss and tough finish.

Specification:

Composition	: Based on oil modified Alkyd Resin and light fast pigments for better gloss and sustained finish.
Covering Capacity	: 16- 18 Sq Meter/ Liter/ Coat.
Film Thickness	: 25-35 Micron per coat.
Application	: Brush, Roller, Spray
Number of Coats	: At least 2 coats should be applied for proper finish and durability
Drying Time	: 1) Surface Dry 1-2 Hours : 2) Touch Dry 2-3 Hours : 3) Recoatable 16 Hours
Thinner	: Mineral Turpentine should be used for application depending on the Substrate and method of application.
Flash Point	: above 73°F
Gloss	: Glossy with silky finish
Colour Range	: As per Rainbow Synthetic Enamel Shade Card
Packing	: 0.91, 3.64 and 14.56 Ltrs.

Application Guide

Wood Work

Smoothen the surface by sand paper and apply a coat of Rainbow Synthetic under Coat followed by filling. After filling is dry sand paper the surface and apply 2 coats of Rainbow Synthetic Enamel. In case the oil is coming out from the wood, remove oil by scraping and seal the oily portion by shellac solution prior to final painting.

Steel Structure

Remove all the rust by sanding, rust removing solution or by flame, and then apply one coat of Red oxide primer followed by 2 coats of Rainbow synthetic enamel.

Note: The above Information is given in good faith, but without any warranty.

Rainbow Paint Industries

Quality & Standard Paint Manufacturer

Head Office:

CI-331, 16-B, Industrial Area,
North Karachi, Karachi.

Ph: 021-36971166, 36971167, Cell: 0321-2111328

Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Regional Office:

House No. 5 Lane No. 1,
Scheme No. 02, PF Chowk

Tipu Road, Chaklala Rawalpindi

Ph: 051-5590971, 051-5591436, 051-5961401