

Rainbow Superflex™ Exterior Wall Primer

Rainbow Superflex Exterior Wall Primer is a high performance elastomeric based emulsion. It is highly washable and alkali resistant with extreme durability. It is able to bridge hairline cracks while offering fast drying and also stops seepage of water and gives good penetrative properties. This is to be used as primary coat to seal and enhance durability of finish paint. It also contains effective additives which protects from fungus for many years. Rainbow Superflex Exterior Wall Primer is an environmental friendly product which is completely free from harmful chemicals such as lead and mercury etc.

Recommended Uses:

Recommended for use in exterior surfaces of concrete, masonry work, brickwork and plasters such as in houses, high rise towers etc. It can be used on high performance interior surfaces.

Product Features:

- Bridges hairline cracks using Superflex™ technology.
- High performance, washability, alkali resistant & durability for exterior applications.
- Quick drying, good penetrative properties & stops seepage of water.
- Low odour & low VOC.
- Environmental Friendly (free from formaldehyde, Nickel, Lead & Mercury etc.)
- Stops & protects from fungus, superior hiding power and spreading /covering rate.

Specification:

Composition:	Based on special pure acrylic emulsion with water proofing & extreme durable properties, pigments & selected extenders.
Covering:	13 – 15 Sq.Meter/Liter/Coat (Depending on surface and nature of plaster)
Thinning Ratio	Depending on Surface & Application Method.
Application:	Brush, Roller and Spray.
No of coats:	Best result are achieved when two coats are applied
Thinner:	Water
Dry Time:	1-3 hours (Depending on the climatic conditions)
Film Thickness:	30 micron
Flash Point:	Not Applicable
Colour:	White
Finish:	Matt
Packing:	0.91, 3.64 and 14.56 Ltrs.
Shelf Life:	Min 18 months approx(unopened, sealed & temperature controlled location)

Note: The above Information is given in good faith, but without any warranty.

Head Office:

CI-331, 16-B, Industrial Area,
North Karachi, Karachi.
Ph: 021-36971166, 36971167, Cell: 0321-2111328
Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Rainbow Paint Industries

Quality & Standard Paint Manufacturer

Regional Office:

House No. 5 Lane No. 1,
Scheme No. 02, PF Chowk
Tipu Road, Chaklala Rawalpindi
Ph: 051-5590971, 051-5591436, 051-5961401

Application Guide

New Concrete Surface

New plaster must be completely clean, dry and free from dirt and grease. Sand down the plaster with Emery stone or emery paper and apply one coat of Superflex Exterior Primer followed by, if required, Rainbow Superflex Exterior Putty. Two coats of putty is applied, with a interval of 2-3 hours between coats. Another coat of Superflex Exterior Primer can also be applied after Wall Putty application.

Old Painted Surface

Remove all dust, dirt and loose adhering or flaked paints by scraping with scraper (wall) or Emery Paper (for wooden surface). After scarping apply 1 coat of Superflex Exterior Primer. Allow to dry properly followed by, if required, 1-2 coats of Rainbow Superflex Exterior Putty prior to application of the finish paint. Another coat of Superflex Exterior Primer can also be applied after Wall Putty application.

Safety & Precautions

- Stir Paint vigorously. Avoid thinning
- Make sure there is ample ventilation available before, during and after
- Keep children and pets away from painted areas and appliances
- When applying paint, it is preferable to wear eye safety goggles and dust mask
- Never leave opened container unattended
- To clean paint from your hands, use soap and water only

Storage & Handling

- Keep away from heat and spark sources, away from direct sunlight.
- Never breathe in dust, mist, gas or vapors from the dry product.
- Keep the containers closed in storage.
- Do not apply during rain/fog/mist/wind or when the temperature is below 5 °C.
- In case of eye contact: Wash with plenty of cold water and immediately consult a physician.
- In case of ingestion: drink plenty of water or milk, do not induce vomiting, & consult a doctor.
- In case of inhalation: remove the person to open fresh air area, provide artificial breathing if needed, and consult a doctor.

Note: The above Information is given in good faith, but without any warranty.

Head Office:

CI-331, 16-B, Industrial Area,
North Karachi, Karachi.

Ph: 021-36971166, 36971167, Cell: 0321-2111328

Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Rainbow Paint Industries

Quality & Standard Paint Manufacturer

Regional Office:

House No. 5 Lane No. 1,
Scheme No. 02, PF Chowk

Tipu Road, Chaklala Rawalpindi

Ph: 051-5590971, 051-5591436, 051-5961401