



## Rainbow Weather Guard Acrylic Emulsion for Exterior

Rainbow weather guard is pure acrylic emulsion paint specially formulated for both tropical climates and climates where heavy rain and extreme temperature variation exists.

This is an exterior finish and also prevents the alkalinity of the masonry works.

## Specification:

Composition

Covering

Film Thickness

Number of Coats

Application

**Drying Time** 

Thinner

Gloss

Color Range

**Packing** 

Surface Preparation

Based on pure acrylic emulsion combined with special

pigments and extenders

300-350 Sq. ft. / Gallon

25-30 micron per coat

2-3 coats

Brush, Roller, Spray

It is recommended to use this paint when temperature is

above 10° C

Recoatable after 2 Hours

Matt with velvet finish

As per Rainbow's Weather Guard Shade Cards

1, 4 & 14.56 Ltrs.

Not much surface preparation is required on exterior surface, however use of Perfecton Wall Primer Sealer will further improve the finish of the paint.

## Application Guide

New Surface: Sand down the plaster with emery stone paper remove the salt, alkali or any efflorence if present by washing with very dilute acid, apply one coat of Rainbow Perfecton Wall Primer Sealer followed by two coats of Rainbow Weather Guard acrylic emulsion.

Old Painted Surfaces: Remove all dust, dirt loose adhering and flacked paints by scraping, apply one thin coat of Rainbow Weather Guard Acrylic Emulsion or Rainbow Perfecton Wall Primer Sealer followed by Rainbow Weather Guard Acrylic Emulsion paint to finish.

**Note:** The above Information is given in good faith, but without any warranty.

Rainbow Paint Industries

Quality & Standard Paint Manufacturer

**Head Office:** 

CI-331, 16-B, Industrial Area, North Karachi, Karachi.

Ph: 021-36971166, 36971167, Cell: 0321-2111328

Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Ph: 051-5590971, 051-5591436, 051-5961401

House No. 5 Lane No. 1, Scheme No. 02, PF Chowk Tipu Road, Chaklala Rawalpindi

Regional Office: