

Rainbow Chlorinated Rubber paint

Chlorinated rubber paint is a medium chemical and acid resistant paint. This can be used on concrete, iron, Zinc, and wood.

Specification:

Composition	Based on chlorinated rubber and combined with inert pigments & extenders, this is single pack product
Covering Capacity	10 -12 Sq Meters/Ltrs./Coat
Film Thickness	25 - 30 Micron per coat
Application	Brush, Spray
Number of Coats	1 or 2 depending on method of application
Surface dry	10-15 Meters
Flash point	73°F
Drying Time	2 Hours
Thinner	Chlorinated rubber thinner
Mixing Ratio	as required for use
Gloss	Glossy to egg shell
Color Range	as Required
Packs	0.91, 3.64, 14.16

Application Guide

No special treatment is required only general surface preparation such as removal, dust, rust and green.

Note: The above Information is given in good faith, but without any warranty.

Rainbow Paint Industries

Quality & Standard Paint Manufacturer

Head Office:

CI-331, 16-B, Industrial Area,
North Karachi, Karachi.

Ph: 021-36971166, 36971167, Cell: 0321-2111328

Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Regional Office:

House No. 5 Lane No. 1,
Scheme No. 02, PF Chowk

Tipu Road, Chaklala Rawalpindi

Ph: 051-5590971, 051-5591436, 051-5961401