

## ***Rainbow Epoxy Enamel G.P.***

A Highly chemical resisting paint for use in industries hospitals and floors where chemical and anticorrosive properties are required. This is much more abrasion resistant than conventional paints.

### ***Specification:***

Composition:	Epoxy resin with polyamide
Mixing Ration:	Paint 2 parts Hardener 1 part
Post Life:	8 hours after mixing (Mixture should be used within 4-6 hours)
Application	Airless/Conventional Spray or brush
Covering capacity	9-10 Sq Meter/Ltrs.
Film Thickness	25-35 Micron DFT
Drying Time.	1. Touch dry 2 Hours 2. Recoatable 16 Hours
Flash point:	73°F
Color:	Assorted Colours.
Packing	4 Ltrs.
Solvent / Cleaner	Thinner 890
Finish	Glossy
Shelf life:	As long the container is kept firmly sealed and at normal temperature the paint life is 12 months

**Note:** The above Information is given in good faith, but without any warranty.

***Rainbow Paint Industries***

#### **Head Office:**

CI-331, 16-B, Industrial Area,  
North Karachi, Karachi.  
Ph: 021-36971166, 36971167, Cell: 0321-2111328  
Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

*Quality & Standard Paint Manufacturer*

#### **Regional Office:**

House No. 5 Lane No. 1,  
Scheme No. 02, PF Chowk  
Tipu Road, Chaklala Rawalpindi  
Ph: 051-5590971, 051-5591436, 051-5961401