



Rainbow Flamboyant Finish

Rainbow Flamboyant finish is high gloss stoving finish with excellent Light fastness.

Specification:

Composition	Rainbow Flamboyant finish is based on Alkyd/Melamine combined with transparent Pigments.
Covering capacity	10-12 sq Meter /LT
Film Thickness	25 Micron (Maximum)
Application	Airless or conventional spray Single coat on stoving aluminum primer
Stoving	120 oc for 30 Minutes P.M. T
Thinner	Rainbow stoving thinner 100
Colour Range	Red, Blue, Green
Shelf life	6 month if kept in sealed container at normal temperature
Surface Preparation	Proper phosphating followed by R stoving aluminum Primer and one coat of Rainbow Flamboyant Finish.

Note: The above Information is given in good faith, but without any warranty.

Head Office:

CI-331, 16-B, Industrial Area,
North Karachi, Karachi.

Ph: 021-36971166, 36971167, Cell: 0321-2111328

Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Rainbow Paint Industries

Quality & Standard Paint Manufacturer

Regional Office:

House No. 5 Lane No. 1,
Scheme No. 02, PF Chowk

Tipu Road, Chaklala Rawalpindi

Ph: 051-5590971, 051-5591436, 051-5961401