

Rainbow Universal Undercoat

Rainbow Universal Undercoat is a multi purpose undercoat which can safely be used under Nitrocellulose Finishing.

This undercoat is specially developed for M.S. and Wood. This is also suitable to be used as filling putty on chip Board used for furniture.

Specification:

Composition	Specially Maleic Modified Alkyd Resin for better flexibility required for wooden structure
Thinner	Mineral Turpentine, NC Thinner
Mixing Ratio	To add for spray viscosity
Application	Spray
Covering Capacity	10-12 Sq. Mtrs / Litter / Coat
Film Thickness	25-30 Micron
No. of Coats	One coat after surface preparation and before Nitrocellulose Finish Paint.
Drying Time	1) S. D. 2hours 2) Recoatable Min. 6 hours - Preferable = O.N.
Flash Point	73°F
Gloss	Matt & Smooth
Colour	White & Grey
Packing	0.91 & 3.64 Ltrs - and in 20 Ltrs Drum on request

Application Guide

Steel Structure

Use one coat of Rainbow undercoat for complete surface preparation to seal oil paint putty, followed by one coat of undercoat prior to application of Nitrocellulose Paint.

Wooden Structure

After the surface is properly prepared use one coat of Rainbow Universal Undercoat and sand down properly and then apply Nitrocellulose Paint.

Note: The above Information is given in good faith, but without any warranty.

Rainbow Paint Industries

Quality & Standard Paint Manufacturer

Head Office:

CI-331, 16-B, Industrial Area,
North Karachi, Karachi.
Ph: 021-36971166, 36971167, Cell: 0321-2111328
Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Regional Office:

House No. 5 Lane No. 1,
Scheme No. 02, PF Chowk
Tipu Road, Chaklala Rawalpindi
Ph: 051-5590971, 051-5591436, 051-5961401