

Power Coat Plus Wall Putty

Power coat plus wall putty is developed for the use on cement plaster for smoothing the surface

Specification:

Composition	Water diluteable Emulsion with special pigments & extender
Covering	Approx 6-7 Sq meter Per Coat depending on surface
No of coats	2 Coats are required for better result
Thinner	Ready to use. Water is used for cleaning utensils
Dry time	Allow 3-4 hours for drying before sanding & recoat
Finish	Matt
Flash point	Not Applicable
Colour	White
Packing	5 & 20 Kg.

Application Guide

Old Surface

Scrape all loose adhering paint film and apply one coat of primer followed by two coats of putty.

New Surface

Power coat plus putty is ready for use however small quantity addition of water may be added in case the plaster is more absorbent.

Note: The above Information is given in good faith, but without any warranty.

Head Office:

CI-331, 16-B, Industrial Area,
North Karachi, Karachi.

Ph: 021-36971166, 36971167, Cell: 0321-2111328

Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Rainbow Paint Industries

Quality & Standard Paint Manufacturer

Regional Office:

House No. 5 Lane No. 1,
Scheme No. 02, PF Chowk

Tipu Road, Chaklala Rawalpindi

Ph: 051-5590971, 051-5591436, 051-5961401